

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Specification Amendments**SAFE AUTO-LOCKING BELAY OVERRIDE MECHANISM**

Abstract: A Safe Auto-Locking Belay Override Mechanism (24) is provided which causes an auto-locking belay device to lock a rope against movement if a belayer panics, as sometimes happens if a climber falls, after the belayer has overridden the normal function of the auto-locking belay device. The mechanism of the subject invention makes use of the realization that a belayer tends to grip an auto-locking belay device tightly when the belayer panics. The subject invention contains a pressure sensitive activation ~~means~~ mechanism that acts on an override ~~means~~ mechanism such that the normal function of the belay device will be overridden by only one of three different force levels. At either relatively low or relatively high levels of force exerted by the belayer on the pressure sensitive activation ~~means~~ mechanism, the auto-locking belay device will function normally and lock a rope against further movement in the event that the rope exerts sufficient force on the auto-locking belay device such as when a climber falls. If, however, the belayer exerts an intermediate level of force on the pressure sensitive activation ~~means~~ mechanism, the normal function of the auto-locking belay device will be overridden such that rope can be fed rapidly through the device.